

Headquarters U.S. Air Force USAF XOR-GANS





Purpose

- Provide Background on Military ADS-B
- Discuss Potential <u>Operational</u> ADS-B Military Unique requirements
- Discuss Potential Military Applications for inclusion in DO-242A
- Discuss Potential Solutions



Objective – Military will seek ADS-B capabilities which:

- ENHANCE SAFETY
- ENHANCE MISSION
- OPEN MISSIONS e.g. Training, Channel, etc
- "SENSITIVE" Missions in which the military may opt to inhibit or encrypt <u>certain</u> parameters e.g. ADS-B listen only mode
- COVERT/CLASSIFIED ADS-B not applicable



- ENCRYPTION
- JAM/SPOOF RESISTANCE

Not unique requirements to military. Other users may desire these features.



- Air Refueling (AR)
- Formation Flying
- ADS-B & TCAS/ACAS
- Air Combat Maneuvering Instrumentation (ACMI)
- Drop Sondes Wind Sondes



<u>Air Refueling (AR)</u> - Large Multi Engine Aircraft (Receivers)

Unique - <u>Intentional proximity of aircraft</u>

AR 101 Phases of Air Refueling

- Rendezvous *
- Closure*
- Contact
- Separation*

^{* =} Possible ADS-B applications



What does the receiver pilot need to know?

- Relative Position of Tanker (Range/Bearing)
- Relative Altitude of Tanker
- Relative Speed of Tanker



RENDEZVOUS


• En route

Pre-coordinated time, location, speed

Point Parallel

Tanker awaits receiver in holding (Anchor)

Rendezvous → "Find the tanker" Position-Altitude-Speed





Rendezvous \rightarrow "Find the tanker"

- Radar (Excellent fighter tool only)
- Radar Beacon
- TCAS/ACAS (ETCAS)
- UHF Direction Finding Hold Down
- ATC Radar
- Referenced Navigation Aids

Position (range/bearing) – Altitude -- Speed

When visual:

• Lighting (at night)





Visual Acquisition to "Contact"

What the pilot needs - POSITION (range) - (ALTITUDE - SPEED)

- Range Information during final closure in meters, then feet **from boom**
 - "Up 1 ... back 3 ... stabilize"
 - (Boom extension range KC-135 is 6 to 18 ft)
- Requires information on navigational center of aircraft
- Meter accuracy in final closure



SEPARATION

- Planned
- Emergency "Beak away 3",

What the pilot needs

Position – Altitude - Speed



<u>IMC FORMATION FLYING</u> Unique – Intentional Proximity of Aircraft

- Large Multi-Engine Aircraft e.g. Hercules (C-130), C-17, KC-10
- IMC capability

Two Systems employed for Formation Station Keeping

• RADAR

- "Coarse" Method
- Aircraft Stacked Vertically
- Relatively Large separation Distances

STATION KEEPING EQUIPMENT

- "Precise" Method
- Co-Altitude
- Relatively Close $\approx 4,000$ ft (1,200 meters)



What does the receiver pilot need to know?


- Deviation Information ... from assigned position
- Situational Awareness ... where are the other aircraft
- Proximity Warning



FORMATION – RADAR

Large Multi Engine – A very coarse tool

(Climbs/Descents, Turns, account for TAS, etc)










SKE – Station Keeping Equipment (Datalink)




4,000ft in-trail spacing between each aircraft



SKE Station Keeping accomplished using:

Primary Flight Display

- Vertical Guidance
- Lateral Guidance
- Longitudinal Guidance



Navigation Display (Horizontal Situation Indicator)

- Station Keeping Guidance
- Situational Awareness

Proximity Warning System

Aural warning on "intruder"









SKE provides

- Deviation Information ... from assigned position
- Situational Awareness ... where are the other aircraft
- Proximity Warning

Radar does not provide above features

SKE


- Accounts for turn effects
- High update rate (>5 times/sec) Integrity
- Datalinks additional information (text, preparatory signals, QNH, leads calculated winds for drops, etc)
- Autopilot Coupled or Manual



Integration of ADS-B and formations

Intra-formation

- •Broadcast rate? Additional parameters/message sets?
- •Designated lead for flight ID?
- •Wingmen slot#?






• Extra-formation

- •One or multiple ADS-B signals from a formation?
 - Conflicting "intent" messages from wingmen?
- •Designated intra formation message sets & broadcast precludes unwanted/unnecessary broadcast to ATC system prevents ATC conflict alert
- •Different intra/extra formation broadcast rate
- •Specify Formation Size/Geometry for other traffic prevents multiple closely spaced & overlapping targets on civilian displays



ADS-B Formation – One or multiple broadcasts?





SKE FORMATION



TCAS limitations for formation








TCAS in Formation

- Lead & Last Aircraft Squawk
- TCAS "single ship" product
- Ships 2 through 5 "blind"
- Lead in TA/RA?



- Wingmen leaderless
- No TCAS guidance
- No situational awareness
- Lead ignores RA
 - Safety implications



Can ADS-B help with its datalink capabilities for TCAS?



Other possible military unique applications

- ACMI Ranges
- Inexpensive Sondes (Airdrop wind gradients)
- Mission following (encryption)